

Description:

Coated paper on both sides with microcapsules on the back and activated clay on the front. It is used as a middle sheet when more than two copies are needed. It can receive and transfer at the same time.

Colors available: White, yellow, blue, pink, green.

End uses:

Business forms, Invoices

Print methods:

Offset

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [ISO 14001 Environment](#)
- [EMAS Leitzta mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Technical specifications

Property	Test Method	Unit	Tolerance	53	60	75	90
Substance	ISO 536	g/m ²	±4%	53	60	75	90
Thickness	ISO 534	µm	±4	71	77	95	110
Opacity	ISO 2471	%	±4	78	81	88	91
Relative humidity	TAPPI T502 OM-89	%	±5	43	43	43	43
Curl	TAPPI T427 UM-85	mm	(4.0)-0.0	-2.0	-2.0	-2.0	-2.0
Whiteness D65/10°	ISO 11475	°CIE	±6	113	113	113	113

GUARANTEES:

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).

5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.

Last update: 06/19/2023